



Cover Systems

Cargo securing

FlexCover – flexible cargo securing from HUESKER



FlexCover: deployment after loading

Variable swivel arms, centrally adjustable

The FlexCover cargo securing system keeps your load safely on the trailer where it belongs during transport. Particularly during the autumn harvest, roads and traffic infrastructures become covered in dirt and debris. Incorrectly secured loads can easily fall or be blown off the trailer. As for the resulting debris, not only do those responsible (service supplier or farmer) have to pay for the cost of cleaning up the area, but it is also hazardous to traffic.

Flexibility

To prevent such situations HUESKER has developed a transport securing system that can be flexibly fitted to almost any trailer. Whether retrofitted or assembled ex-works, the FlexCover cargo securing system can be optimally adjusted to fit any trailer height. FlexCover offers ideal protection particularly in the case of lightweight bulk goods, which as a result of adverse weather or road conditions may cause hazards on the roads. As a consequence, not only is the letter of the law upheld, the cost of cleaning up the mess is also avoided.

Swivel arms

The angle of the swivel arms can be centrally adjusted so that they run above the openable tailgate and do not need to be manoeuvred inconveniently past the tailgate. Furthermore, when the trailer volume is expanded for harvesting, the swivel arms can also be altered to fit the respective trailer height through a simple adjustment and without any need for refitting.

Compact design

Another advantage of FlexCover is the system's compact design, which leaves no projecting components after fitting.



Cover systems

Cargo securing



Transportation with FlexCover



Flexible swivel arm



Guided above the tailgate

That rules out getting anything caught on branches or trees and prevents deformation of the trailer body. Trailer dimensions are not exceeded or expanded as a result of fitting the FlexCover system.

Drive

The FlexCover cargo securing system is powered by a hydraulic oil motor, which can be connected to almost any agricultural tractor unit. As such, no modification of the tractor electronic system is required. The tractor's existing connections and control components can be used to operate the system.



Hydraulic oil motor with standard connections

Trailer dimensions are not exceeded

FlexCover benefits at a glance:

- Flexible system design
- Can be easily adapted to various trailer heights
- Perfect for retrofitting onto existing trailers
- Also suitable for assembly ex works
- The system is guided above the tailgate
- The hydraulic drive ensures easy coupling to the tractor unit

For further information on product features or applications please contact us and visit our website at www.HUESKER.com.

HUESKER Synthetic GmbH

Fabrikstraße 13-15
D-48712 Gescher, Germany
Phone: +49 (0) 25 42 / 7 01-0
Fax: +49 (0) 25 42 / 7 01-499
E-mail: info@HUESKER.de
Internet: www.HUESKER.com

Click here
View Video!



DAR-PL-3226/00
Akkreditiert nach DIN EN ISO/IEC 17025